



PLAN VIEW

DUAL METER SERVICE PEDESTAL

TYPICAL APPLICATION: WHERE LOADS ARE BILLED AT DIFFERENT RATES OR BILLED TO DIFFERENT ACCOUNTS

STANDARD FEATURES

- (2) METER SOCKETS WITH TEST BLOCKS 4 JAW UTILITY LANDING LUGS 250 KCMIL
- STANDARD VOLTAGE 120/240VAC 1 PHASE 3 WIRE
- CIRCUIT BREAKER INTERIOR COPPER BUS
- (2) 12 CIRCUIT 100 OR 200 AMPS, (1) INTERIOR PER METER OR
- (3) 8 CIRCUIT 100 AMPS, (1) INTERIOR PER METER AND
- (1) UNMETERED INTERIOR OR
- (2) 8 CIRCUIT 100 AMPS, (1) INTERIOR PER METER

SPECIFICATIONS

- * COMPLIES WITH EUSERC STANDARDS & DWG. 308
- * NEMA 3R CONSTRUCTION
- * POLYESTER POWDER-COATED FINISH EXCEEDS ASTM B-117 SPECIFICATIONS
- * FABRICATED FROM CORROSION-RESISTANT ZINC COATED STEEL
- * AVAILABLE IN ALUMINUM & STAINLESS STEEL

- * LIGHT GREEN COLOR NO. 14672 PER FEDERAL SPECIFICATIONS 595 -
- * ALL FACTORY WIRING 600 VOLT RATED COPPER
- * ALL COMPONENTS UL LISTED
- * ALL EXTERIOR DOORS AND COVERS PADLOCKABLE
- * UTILITY COVERS SEALABLE
- * AUXILIARY CABINETS AVAILABLE (20-IN. & 30-IN. WIDE)